


MH140 PCB Terminal Block, High Power- Modular



DIMENSIONS/POSITIONS

DIMENSIONS/POSITIONS		MH140-635	MH140-635M
間距	Pitch	6.35mm	6.35mm
位數	Poles	2 ~ 8Poles	2 ~ 30Poles
塑膠本體	Housing Material	PA 66	PA 66
壓線圈	Cage Clamp	Steel, Zinc Plated	Steel, Zinc Plated
端子	Contact	Copper, Tin Plated	Brass, Tin Plated
螺紋	Screw Thread	M3, Steel, Zinc Plated	M3, Steel, Zinc Plated
電線線徑	Wire Size	8 ~ 18AWG	8 ~ 18AWG
剝線長度	Wire Strip Length	6.5mm ~ 7.5mm	6.5mm ~ 7.5mm
PCB孔徑	PCB Hole Diameter	1.6mm	1.6mm
最大緊固扭矩	Tightening Torque, Max.	9.0 Lb-in	9.0 Lb-in
環境作業溫度	Operating Temperature	-40°C to +105°C	-40°C to +105°C

TECHNICAL DATA

連接符合標準 Connection in acc. with standard EN-VDE			
額定電流 I _n	Nominal Current I _n	57A	57A
額定橫截面	Nominal Cross Section	10mm ²	10mm ²
最大負載電流	Maximum load current	57A	57A
絕緣材料	Insulating Material	PA	PA
阻燃等級,符合UL94 Inflammability class acc. to UL94		V0	V0
額定電壓,UL/CUL Nominal voltage, UL/CUL		600V	600V
額定電流,UL/CUL Nominal current, UL/CUL		35A	35A

